



PRODUCT BROCHURE

CIRCULATING WATER BATH: HSN Code: 8418

This Circulating Water Bath is double walled construction & duly insulated by best quality glass wool to avoid Loss of temperature of the working chamber. Inner chamber is made of Stainless Steel (304grade) & outer body made of Mild Steel sheet finished with Powder coated paint.

Construction: Double walled. Inner chamber made of Stainless Steel Sheet and outer chamber made of Mild Steel Sheet finished with Powder Coating paint. All sides are Argon welded. The gap between two walls insulated by glass wool to prevent the heat loss.

Refrigeration System: Refrigeration unit is complete with Hermetically sealed type compressor C.F.C FREE REFRIGERANT, Air cooled condenser with copper tubes and aluminum fins, Evaporator, High Low cut-out switch, Single Phase Preventer, Starter and Time Delay etc. Maintaining 0°Cto25° temperature and controlled by Digital Temperature Indicator cum Controller Electrically operated on 220 /230volts, single phase, A.C. mains
LIQUID MEDIA HAS TO BE SUPPLIED BY THE INDENTOR/PURCHASER



Mobility: Castor will is provided at the bottom of the Equipment for easy mobility

Power: To work on 220 volts A.C. mains ,1Phase

Pump Flow: 15Litre / minute or Pump Flow: 30Litre / minute

Cooling Capacity: 400watts

Recommended to use the Instrument ,on a Air-conditioned Room.

TECHNICAL SPECIFICATION:

Temp Range.	0°C to 25°C
Temp Accuracy.	±1.0°C
Temp Control.	Microprocessor Based Digital Temp Controller (LED Dispaly)
Capacity	6 to 8 Ltr

Brand: NR , Model: NR/CB-15

Brand: NR , Model: NR/CB-30

Declaration: This product is exclusively manufactured/ assembled in India. Spares are easily available & repairable . Any dispute Kharagpur/Midnapur(W) jurisdiction only.

NABARUPAYAN

P.O. Hijli Co-operative, Prembazar,
Kharagpur-721306,W.B.

E-mail: nabarupayan@gmail.com

